



INVICTUS

# MAXIMUS Dryback

Technical Specification		Maximus Dryback	Maximus Loose Lay
Description		Heterogeneous pvc	Heterogeneous pvc
Thickness	EN ISO 24337	2.50 mm	5.00 mm
Wearlayer	EN ISO 24340	0.55 mm	0.55 mm
Wearlayer PUR coating		Scratchmaster® top layer	Scratchmaster® top layer
Weight per sqm	EN ISO 23997	ca. 4310 g/m <sup>2</sup>	ca. 9700 g/m <sup>2</sup>
Classification	EN ISO 10874	23 Domestic Heavy - 33 Commercial Heavy - 42 Industrial General	



## Performance

Reaction to fire	EN 13501-1	Bfl-S1	Bfl-S1
Slip resistance	EN 13893	DS	DS
Slip restraint (dynamic coefficient of friction)	DIN 51130	R10	R10
Thermal resistance R value	EN 12664	0.028 (m <sup>2</sup> .K)/W	0,05 (m <sup>2</sup> .K)/W
Underfloor heating	EN ISO 12524	Yes, max. 27°C	Yes, max. 27°C
Electrostatic performance	EN 1815	< 2 kV (antistatic)	< 2 kV (antistatic)
Residual indentation	EN ISO 24343-1	< 0.1 mm	< 0.1 mm
Dimensional stability	EN ISO 23999	≤ 0.15%	≤ 0.15%
Curling	EN ISO 23999	pass	pass
Castor chair resistance	EN ISO 4918	pass, Type W	pass, Type W
Colour fastness	EN ISO 105-B02	> 6	> 6
Micro Scratch Resistance	EN 16094	-	≤ MSR-A1 / ≤ MSR-B1
Impact sound insulation (ΔLw)	EN ISO 717-2	3dB (ΔLw)	approx. 7dB (ΔLw)
Chemical / Stain resistance	EN ISO 26987	pass	pass
Abrasion resistance	EN ISO 660-1	class T	class T
Indoor AIR quality - French VOC regulation	ISO 16000	Greenguard GOLD - Floorscore - A+	
Content of pentachlorophenol		PCP under detection limit	
Formaldehyde emissions (28 days test)	EN ISO 717-1	NA HCHO (has not been added)	
Phthalate free		Yes, biobased	Yes
CE marking	EN 14041:2011		

## Packaging

Size and packaging wood	EN ISO 24342	178x1219mm / 15 planks = 3,252 m <sup>2</sup> /carton	229x1219mm / 6 planks = 1,672 m <sup>2</sup> /carton
Size and packaging wood	EN ISO 24342	228x1219mm / 12 planks = 3,340 m <sup>2</sup> /carton	-
Size and packaging XL plank	EN ISO 24342	228x1500mm / 10 planks = 3,429 m <sup>2</sup> /carton	-
Size and packaging XL plank	EN ISO 24342	241x1517 mm / 10 planks = 3,660 m <sup>2</sup> /carton	-
Size and packaging Parquet	EN ISO 24342	102x406mm / 34 planks = 1,404 m <sup>2</sup> /carton	-
Size and packaging Herringbone	EN ISO 24342	150x749mm / 30 planks = 3,369 m <sup>2</sup> /carton	-
Size and packaging tile	EN ISO 24342	229x229mm / 40 tiles = 2,09 m <sup>2</sup> /carton	-
Size and packaging tile	EN ISO 24342	305x610mm / 18 tiles = 3,345 m <sup>2</sup> /carton	-
Size and packaging XL tile	EN ISO 24342	610x610mm / 10 tiles = 3,716 m <sup>2</sup> /carton	-
Size and packaging XL tile	EN ISO 24342	457x914mm / 8 tiles = 3,345 m <sup>2</sup> /carton	457x914mm / 4 tiles = 1,672 m <sup>2</sup> /carton

## Warranty

Warranty	25 years Residential / 15 years Commercial
----------	--

The technical data is correct at the time of printing. - 11/2025

